

Safety Data Sheet

(EN / D)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019

Version (Revision) : 4.0.1 (4.0.0)

Print date : 13.02.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lithofin Steel-Clean

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Mixture Care Product, contains: organic solvents

1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)

Distributor :

Casdron Enterprises Ltd.

Street :

Wood End, Prospect Road

Postal code/city :

GB- New Alresford, Hants SO 24 9QF

Telephone :

+44 1962 732126

Telefax :

+44 1962 735373

Contact :

Technical Department

E-mail: sales@lithofin.co.uk

Emergency telephone number:

0196 2732126

(Only available during office hours)

Supplier :

Lithofin AG

Street :

Heinrich-Otto-Str. 36

Postal code/city :

73240 Wendlingen

Telephone :

+49 (0)7024 9403-0

Telefax :

+49 (0)7024 9403-40

Contact :

Technical Department

E-mail: info@lithofin.de

Emergency telephone number:

+49 (0)7024 9403-0

(Only available during office hours)

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1 ; H222 - Aerosols : Category 1 ; Extremely flammable aerosol.

Aerosol 1 ; H229 - Aerosols : Category 1 ; Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02)

Signal word

Danger

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019

Version (Revision) : 4.0.1 (4.0.0)

Print date : 13.02.2019

Hazard statements

- H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local and national regulations.

Supplemental Hazard information (EU)

- EUH066 Repeated exposure may cause skin dryness or cracking.

Special rules for supplemental label elements for certain mixtures

- EUH208 Contains (R)-P-MENTHA-1,8-DIENE. May produce an allergic reaction.

Other labelling

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; REACH registration No. : 01-2119457273-39-xxxx ; EC No. : 918-481-9; CAS No. : (64742-48-9)

Weight fraction : $\geq 45 - < 50$ %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

(R)-P-MENTHA-1,8-DIENE ; REACH registration No. : 01-2119529223-47-xxxx ; EC No. : 227-813-5; CAS No. : 5989-27-5

Weight fraction : $\geq 0,1 - < 0,25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

No special measures are necessary.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

None

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

None

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019

Version (Revision) : 4.0.1 (4.0.0)

Print date : 13.02.2019

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

None

6.2 Environmental precautions

None

6.3 Methods and material for containment and cleaning up

None

6.4 Reference to other sections

None

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Protective measures****Measures to prevent fire**

Fire class : C

7.2 Conditions for safe storage, including any incompatibilities**Hints on joint storage**

Storage class (TRGS 510) : 2B

Recommended storage temperature 5 - 25 °C

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 600 mg/m³

Version :

BUTANE ; CAS No. : 106-97-8

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 1000 ppm / 2400 mg/m³

Peak limitation : 4(II)

Version : 01.03.2018

PROPANE ; CAS No. : 74-98-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 1000 ppm / 1800 mg/m³

Peak limitation : 4(II)

Version : 01.03.2018

ISOBUTANE ; CAS No. : 75-28-5

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 1000 ppm / 2400 mg/m³

Peak limitation : 4(II)

Version : 01.03.2018

(R)-P-MENTHA-1,8-DIENE ; CAS No. : 5989-27-5

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 5 ppm / 28 mg/m³

Peak limitation : 4 (II)

Remark : H, Sh, Y

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019

Version (Revision) : 4.0.1 (4.0.0)

Print date : 13.02.2019

Version : 01.03.2018

8.2 Exposure controls

Personal protection equipment

Skin protection

Hand protection

Suitable material : NBR (Nitrile rubber), 0,4mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : gaseous

Colour : colourless

Odour : perfumed

Safety relevant basis data

Melting point/melting range :	(1013 hPa)	<	-13	°C	
Initial boiling point and boiling range :	(1013 hPa)		not determined		
Decomposition temperature :	(1013 hPa)		not determined		
Flash point :		<	0	°C	closed cup (EN ISO 3679)
Ignition temperature :			not determined		
Sustaining combustion			Yes		UN Test L2:Sustained combustibility test
Lower explosion limit :			not determined		
Upper explosion limit :			not determined		
Vapour pressure :	(50 °C)	<	3000	hPa	
Density :	(20 °C)		0,68	g/cm ³	Pyknometer (DIN EN ISO 2811-1)
Water solubility	(20 °C)		immiscible		
pH :			not applicable		DIN 19268
log P O/W :			not determined		(Mixture)
Flow time :	(23 °C)		not applicable		ISO cup 4 mm (DIN EN ISO 2431)
Odour threshold :			not determined		
Vapourisation rate :			not determined		
VOC content-EC		approx.	91,2	Wt %	*
VOC-France			not applicable		Décret no 2011-321 du 23 mars 2011

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019
Print date : 13.02.2019

Version (Revision) : 4.0.1 (4.0.0)

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50 ((R)-P-MENTHA-1,8-DIENE ; CAS No. : 5989-27-5)
Exposure route : Oral
Species : Rat
Effective dose : 4400 mg/kg
Parameter : LD50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Exposure route : Oral
Effective dose : > 5000 mg/kg

Acute dermal toxicity

Parameter : LD50 ((R)-P-MENTHA-1,8-DIENE ; CAS No. : 5989-27-5)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/kg
Parameter : LD50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Exposure route : Dermal
Effective dose : > 5000 mg/kg

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Chronic (long-term) fish toxicity

Parameter : NOEC (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Fish
Effective dose : > 0,1 - 1 mg/l

Chronic (long-term) daphnia toxicity

Parameter : NOEC (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Daphnia
Effective dose : > 0,1 - 1 mg/l

Acute (short-term) algae toxicity

Parameter : EC50 ((R)-P-MENTHA-1,8-DIENE ; CAS No. : 5989-27-5)
Species : Daphnia
Effective dose : 17 mg/l
Exposure time : 48 h
Parameter : EC50 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Daphnia
Effective dose : > 100 mg/l

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019

Version (Revision) : 4.0.1 (4.0.0)

Print date : 13.02.2019

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Waste code (EWC/AVV) : 16 05 04*

SECTION 14: Transport information

14.1 UN number

UN 1950

14.2 UN proper shipping name

Land transport (ADR/RID)

AEROSOLS

Sea transport (IMDG)

AEROSOLS

Air transport (ICAO-TI / IATA-DGR)

AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 2
Classification code : 5F
Hazard identification number (Kemler No.) : 23
Tunnel restriction code : D
Special provisions : LQ 1 | E 0
Hazard label(s) : 2.1

Sea transport (IMDG)

Class(es) : 2.1
EmS-No. : F-D / S-U
Special provisions : LQ 1 | E 0
Hazard label(s) : 2.1

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 2.1
Special provisions : E 0
Hazard label(s) : 2.1

14.4 Packing group

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin Steel-Clean

Revision date : 30.01.2019

Version (Revision) : 4.0.1 (4.0.0)

Print date : 13.02.2019

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to AwSV

Other regulations, restrictions and prohibition regulations

Switzerland

VOCV-Regulation

Maximum VOC content (Switzerland) : 91,2 Wt % according to VOCV

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

07. Hints on joint storage - Storage class

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.