

## Lithofin WAX-OFF Wax and Oil Remover

### Description

Lithofin WAX-OFF is a versatile, ready-to-use cleaner based on a highly active combination of solvents and cleaning components.

#### Technical Data:

Density: ca. 0,82 g/cm<sup>3</sup>

pH-Value: n.a.

Appearance: liquid, clear

Odour: aromatic, orange-like

Flash Point: approx. 39°C

Solubility in Water: emulsifiable

### Properties

Lithofin WAX-OFF dissolves organic dirt such as wax, oil, grease, tar, fresh paint, sealants, care product residues, etc. and allows them to be removed with water.

### Field of Use

For removing oily and greasy dirt deposits from solvent resistant surfaces such as natural and concrete stone, ceramics, clay and quarry tiles, concrete, etc. Suitable for indoor and outdoor use. Also suitable for removing elastic joints (silicone).

### Directions for Use

Apply Lithofin WAX-OFF undiluted to the dry surface and distribute evenly. Work in small controlled sections. Allow the product to work for 5 to 20 minutes, brushing occasionally. Do not allow to dry. When all deposits are dissolved, add some water, brush and remove the solution from the surface. On large surfaces use a squeegee or a wet and dry vac. Always rinse well with clear water. In case of stubborn deposits, repeat this procedure when the surface has dried.

**Please Note:** the surface temperature must not exceed 25°C. Switch off under floor heating. Solvent sensitive surfaces such as rubber, paint, varnish, linoleum, asphalt, some plastics, etc. must be protected against splashes. Always try the product in an inconspicuous area prior to use.

**Advice:** in case of deep oil stains on natural and artificial stone, we recommend Lithofin OIL-EX.

**Coverage:** approx. 7 to 15m<sup>2</sup> depending on type and stubbornness of the deposits.

### Storage

Keep cool, closed and dry.

Shelf life of up to 4 years.

### Environmental Protection

Surfactants are biologically degradable in accordance with EU-regulations. Free of chlorinated hydrocarbons.

**Disposal:** Containers are made of environmentally friendly tin plate. Clean containers can be recycled through collection systems.

### Safety

**Ingredients:** >30% aliphatic and aromatic hydrocarbons, 5 - 15% non-ionic surfactants, limonene, auxiliary agents.

**Labelling according to EU-Directive 1272/2008(CLP):**

GHS Symbol 02, 05, 07, 08, 09 Danger

Hydrocarbons. Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local and national regulations.

ADR 2015: labelling for transport

Unit	Label	Notes on freight papers
a, b	UN1993	none, due to limited quantities

### Packaging

**a)** 1 litre bottle with child-proof cap (10 bottles per box)

**b)** 5 litre canister (2 canisters per box)

Please note: information about environmental protection and safety applies to the (concentrated) product as delivered. When the product is diluted, these properties may change.

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (EN2.16gps/1.13)