

Lithofin MN Slate Oil

Description

A special product from the LITHOFIN-Range for marble and natural stone (MN). The ready-to use protective and care treatment contains high quality waxes and resins in CFC-free solvents.

Properties

Lithofin MN Slate Oil invigorates the stone's colours thereby accentuating the natural structure of the material. Surfaces appear livelier and become water resistant. Lithofin MN Slate Oil develops an elegant sheen which can be increased through polishing. The colour intensification of the product conceals stains which may be in the surface. Thick layers are not formed because a large portion of the old coat is removed when the product is reapplied. Lithofin MN Slate Oil is therefore suitable for regular maintenance work.

Technical Data:

Density: approx. 0.8 g/cm³

pH-Value: n.a.

Appearance: liquid, colourless, clear

Odour: aromatic

Flash Point: >23°C

Solubility in Water: not soluble

Field of Use

For initial treatment of newly installed surfaces such as stairs, table tops, window sills, etc. Achieves a fresh look and protects the surface. Also suitable for touching up slate surfaces which have faded in colour. Highly suitable for regular care in order to maintain the colour-intensive appearance.

Surfaces: rough to finely honed clay slate surfaces, especially Indian, African and Italian slates. For indoor use only.

Directions for Use

Shake bottle before use.

Newly installed surfaces: the surface to be treated must be completely dry. Evenly and generously apply Lithofin MN Slate Oil with a sponge or cloth and allow it to dry.

Dirty and pre-treated surfaces: Apply generously and, after a few minutes, remove the dissolved residues with a cloth. Then apply again and allow to dry.

Please Note: always try the product in an inconspicuous area prior to use. The gloss level can be increased through polishing. If you are not satisfied with the result, apply again ensuring even distribution. In temperatures below 10°C, the product may separate or discolour. In this case, store the bottle in a warm place and shake until the product has turned clear again.

Drying Time: approx. 10 minutes.

Coverage: approx. 20m² per litre depending on the surface.

Further Maintenance

Lithofin MN Slate Oil is suitable as a maintenance product due to its cleaning properties. In case of stubborn dirt deposits, use Lithofin MN Power-Clean. For regular maintenance, we recommend Lithofin MN Wash & Clean or Lithofin EASY-CARE.

Storage

Keep closed and dry. In temperatures between 10°C and 25°C. Shelf life of up to 3years.

Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate.

Clean containers can be recycled through collection systems.

Safety

Ingredients and aromatic hydrocarbons; waxes; auxiliary agents.

Labelling according to EU-Directive 1272/2008(CLP):

Symbol GHS 02, 07, 08, 09 Danger

Hydrocarbons, n-alkanes, iso-alkanes, cyclics. Flammable

liquid and vapour. May be fatal if swallowed and enters

airways. May cause drowsiness or dizziness. Toxic to

aquatic life with long lasting effects. Repeated exposure

may cause skin dryness or cracking. Keep out of reach of

children. Keep away from heat/sparks/open flames/hot

surfaces. – No smoking. IF SWALLOWED: Immediately call

a POISON CENTER or doctor/physician. Do NOT induce

vomiting. Store locked up. Dispose of contents and

container in accordance with local and national regulations.

ADR2003

Unit	Label	Notes on freight papers
a), b)	LQ	none, due to limited quantities

Packaging

a) 1 litre bottle with child-proof cap (10 per box)

b) 5 litre canister (2 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated).

This information should be considered to be informal and non-binding.

The products must be used according to local conditions and materials.

Always test the product in an inconspicuous area. (GB11.15gps/8.15)

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · sales@lithofin.co.uk

Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de

www.lithofin.co.uk