

Treatment of Porphyry rough -outdoors-

Porphyry is an effusion rock (rhyolite) of various origins. Trentino and South Tyrolean porphyry are often used. It usually has a reddish-brown colour and is often laid with a rough surface. All coverings retain their naturally beautiful appearance thanks to a natural stone-friendly treatment. Please note the following information.

Before grouting

To make it easier to wash off the grout on rough surfaces, apply Lithofin STAINSTOP >W<* thinly before grouting.

Final construction cleaning



A clean, clear surface can be obtained by cleaning with Lithofin MN Builders' Clean. They remove cement residue and other construction dirt at the same time. Dilute the cleaner to approx. 1:7, apply to the pre-wetted surface, brush through after a few minutes and then rinse off with plenty of water.

Removal of special contaminants

oil, grease dirt	Lithofin MN Power-Clean
wood stains, wax, tar, sealants	Lithofin WAX-OFF
deep-seated oil stains	Lithofin OIL-EX
vegetable discoloration	Lithofin MN Outdoor Cleaner**
green pavements,	Lithofin ALGEX**

** Use biocides safely. Read labeling and product information before use.

Regular maintenance

Natural stone does not require any special care. Under normal use, it is sufficient to sweep the covering and scrub wet from time to time. Add Lithofin MN Power-Clean to the mopping water, especially after winter (spring cleaning).



LITHOFIN special products for marble and other natural stones are only available in natural stone retailers.


Technical Support Line at 0049 (0)7024 9403-20

This information can and should only provide non-binding advice. The use of a product must be adapted to the local conditions and the surfaces to be treated. The suitability of the product shall be determined on a test area.

EN7.26 / Ref. 41020 Edition 3.20as

Additional protective treatment

Surface treatment improves the appearance and performance properties of natural stone. This results in fewer stains or stains and other contaminants are easier to remove. The natural stone surface is much easier to maintain and remains beautiful for years.



△ **Important:** All impregnations must only be used on completely dried and absorbent surfaces.

Waiting times:

4-6 weeks for installation in mortar bed, 2-3 weeks for thin-bed installation. The creation of a test area is recommended.

A repeat of the treatment after a few years ensures the optimal protective effect.

There are two options to choose from:

1) Without color recess – without gloss

Lithofin MN Stain-Stop* is an open-pored Impregnation and equips the surface oil, grease and water repellent. Therefore, there are fewer stains and maintenance cleaning is sustainable. lighter. This type of treatment is ideal if the pavement is visually unspoiled. should remain changed.



Processing: Easy with surface brush, Apply the sealing brush or roller generously and evenly, let it soak in and remove any excess completely before drying (approx. 15 minutes).

Coverage: approx. 15m² / litre.

Alternatively, the low-odour, solvent-free Lithofin STAINSTOP >W<* can be used. For industrial and professional use only.

2) With color deepening – without shine

Lithofin MN Colour Intensifier gives the flooring a strong colour *** (like wet) and a fresh look. At the same time, the covering is protected against water absorption.

Application: Apply Lithofin MN Colour Intensifier with a surface brush, roller or sealing brush generously and evenly.

Coverage: approx. 10 m²/Litre.



*****Note:** On pre-impregnated surfaces, the colour deepening with Lithofin MN Colour Intensifier is visibly lower.

*For industrial and professional use only.

The Professional Solution

Manufactured in Germany by:

LITHOFIN AG · 73240 Wendlingen · Phone: +49 7024 9403-0 · e-mail: info@lithofin.de · www.lithofin.com