Treatment of **Anröchter stone** -all surfaces-

Anröchter Stein is a clayey-bound limestone with a characteristic green or blue hue.
The use also includes floor and wall coverings. As with any natural stone, the right treatment is important from the very beginning and ensures the good appearance of this timeless natural stone for many years.

General information

All calcareous stones are attacked by acidic substances such as vinegar, wine, sparkling wine, lemon juice, acidic cleaners, etc. and get dull or light spots. Therefore, avoid the contact of these substances with polished or ground surfaces. You should also avoid scratching, abrasive pot cleaners and scouring powders or the like.

Before grouting

Apply the impregnation you want later to the dry-as possible covering 1x thinly before grouting. The resulting water repellency makes it easier to wash off the grout from the covering.
△ Please note that cement film removers contain acids and are not suitable for polished and sanded surfaces. When grouting, careful washing with water is therefore necessary.

Final construction cleaning



To obtain a clean and clear surface, you should clean by wiping with Lithofin MN Power-Clean 1:10 diluted. For rough surfaces, you can also use Lithofin MN Builders' Clean highly diluted (min. 1:20).

Residues of grout on sanded surfaces: Apply Lithofin MN Power-Clean at least 1:3 diluted, leave on for approx.10 minutes and rub off carefully with a white pad without pressure.

Special contaminants

Oily, greasy impurities as well as residues of care products can be easily removed with Lithofin MN Power-Clean. In stubborn cases, also for tar, wax, wood glazes, sealants, etc., use Lithofin WAX-OFF. For deep-seated oil and grease stains, use Lithofin OIL-EX. Limescale deposits can only be removed mechanically with a scraper, razor blade or similar.

LITHOFIN special products for marble and other natural stones are only available in natural stone retailers.
Technical Support Line 0049 (0)7024 9403-20

EN7.26 / Ref. 43040 Edition D3.20as

Additional easy-care equipment

In general, we recommend a special impregnation for used surfaces such as floors, walls, tables, countertops. This makes the surface water and oil repellent, so that discoloration caused by moisture and stains caused by oil, grease and the like are largely avoided or easier to remove. This makes Anröchter Stone even easier to care for and remains beautiful and well-groomed for years.

△ **Important:** Treatments may only be processed on completely dried out and absorbent surfaces. The creation of a test area is recommended.

The processing of impregnations is simple: Apply evenly with a mop or brush, allow to absorb and remove excess completely before drying (approx.15 minutes).

Lithofin STAINSTOP >W<* is suitable for all surfaces. A repeat of the impregnation after about 3 years is recommended. The active ingredients are harmless to health.

Regular maintenance

Under normal use, regular, damp wiping is sufficient. Add Lithofin MN Wash & Clean to the mopping water – so you clean and care at the same time.
△ Highly grease-dissolving agents and leaching soft soaps are not suitable for long-term care.

This information can and should only provide non-binding advice. The use of a product must be adapted to the local conditions and the surfaces to be treated. The suitability of the product shall be determined on a test area.

*For industrial and professional use only.

Your LITHOFIN-Dealer:

The Professional Solution

Manufactured in Germany by:
LITHOFIN AG · 73240 Wendlingen · Phone: +49 7024 9403-0 · e-mail: info@lithofin.de · **www.lithofin.com**