

Caring for and maintaining Slate in the Bathroom

Characteristic of the clay slate is its good cleavage. This creates rustic and natural-looking surfaces with correspondingly non-slip properties. Occasionally, the panels are also sanded. Regardless of the surface condition, every surface requires a certain amount of care.

General information

Please note that chlorite slate and some clay slates, e.g. black ones from Italy, contain limestone admixtures and are sensitive to acids. Therefore, avoid acidic cleaners and substances getting on the surface. This would cause bright spots.

Additional easy-care equipment



In bathrooms and similar systems, we generally recommend impregnation with Lithofin MN Stain-Stop. This makes the flooring water- and oil-repellent and thus protects it against stains in the best possible way. The beautiful new appearance of the surface is retained for years – and with the least amount of maintenance. For industrial and professional use only.

Lithofin MN Stain-Stop is suitable for rough splitting and ground surfaces. The appearance does not change, a slight deepening of the color may occur. The processing is simple.

△ Important: Impregnations can only be used on completely dried and absorbent surfaces. The creation of a test area is recommended.

The impregnation should be repeated once a year in the wet-contaminated areas.

The recommended products are optimally matched to each other and support the effect of the impregnation. The health safety was confirmed by an independent institute in accordance with the provisions of the LFGB and EU Regulation 1935/2004.

Regular maintenance



Under normal use, it is sufficient to wipe the coverings regularly with a damp cloth. Always add a dash of Lithofin MN Wash & Clean to the mopping fluid to clean and care for at the same time. You can clean and care for small areas particularly effortlessly with Lithofin MN Easy-Clean and strengthen the protective effect impregnation. Simply spray on and wipe with a damp cloth.



Additional care:

Stressed small areas such as washbasins occasionally with Lithofin MN Slate Oil treat. This gives the surface additional protection and shine.

Tip: You should always wipe off water splashes, especially hard water, as well as creams, lotions, soap residues, etc. as soon as possible to prevent stains. Under no circumstances should leaching soft soaps or strongly grease-dissolving agents be used.

Once limescale deposits have formed, they must be removed from acid-resistant natural stone surfaces with Lithofin KF Ceramic-Clean. For sensitive clay slates, carefully rub off such residues with Lithofin MN Power-Clean and white pad.

LITHOFIN special products are only available from specialist retailers for tile and natural stones. If you have any questions or questions, please contact the **Technical Support Line at 0049 (0)7024 9403-20**

This information can and should only provide non-binding advice. The use of a product must be adapted to the local conditions and the surfaces to be treated. The suitability of the product shall be determined on a test area.

EN7.26 / Ref. 44003 Edition D3.20as

Your LITHOFIN-Dealer:

■ The Professional Solution

Manufactured in Germany by:

LITHOFIN AG · 73240 Wendlingen · Phone: +49 7024 9403-0 · e-mail: info@lithofin.de · www.lithofin.com