

## Cleaning and Maintaining Porcelain Tiles -outdoors-

Instructions for tiles with matte finishes

Porcelain tiles are made of very fine ceramic materials that are fired at high temperatures. This process leads to very dense, very robust tiles. The right treatment will bring the tiles to their full potential and ensures the ideal properties for many years.

### Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1a

#### Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin KF Cement Residue Remover leaves a clean and clear surface.



Coverage:  
1 Ltr./30m<sup>2</sup>



Dilute product 1:4  
with water.



Wipe surface with  
solution.



Rinse well with  
plenty of clear water  
and towel dry.


**Erforderliche Geräte:** Eimer, Mopp und Schrubber, Gummiabzieher oder Wassersauger

1b

#### Initial cleaning -drainable mortar- 1-component systems



Coverage:  
1Ltr./30m<sup>2</sup>



Dilute product 1:5  
with water. apply to  
the surface and allow  
to work for 20 min.  
(20°C surface tem-  
perature). Scrub oc-  
casionally.



Rinse well with  
plenty of water.

1c

#### Initial cleaning -drainable mortar- 2-component systems



Coverage:  
1 Ltr./5m<sup>2</sup>



Apply the undiluted  
product to the surface  
and allow to work for  
60 min. (20°C surface  
temperature): Scrub  
occasionally.



Rinse well with plenty  
of water.

**Necessary equipment:** bucket, mop, scrubbing brush.

2

#### Regular maintenance


Lithofin KF Intensive Cleaner maintains porcelain tile surfaces.



Add one squirt  
(20ml) to one bucket  
of water.



Wipe or scrub the  
surface with the  
solution and rinse  
well.



Allow to dry. Do not  
walk on surface dur-  
ing drying time.

**Necessary equipment:** bucket, mop.

Please follow the detailed instructions on the product labels.

Ref. 22002 2.21gps

### Cleaning and refurbishing used or extremely dirty surfaces

Lithofin MN Outdoor Cleaner is a chlorine based, alkaline product with high-quality cleaning components. This special cleaner is suitable for a regular basic cleaner and removes all types of common dirt.

- Apply undiluted.
- Distribute with a scrubbing brush or mop.
- Allow to work for approx. 20 min., scrubbing occasionally. Do not allow to dry.
- Remove the solution from the surface and rins well with plenty of water.

### Other, stubborn types of dirt

Grease, oil, wax, tar, paint, rubber streaks	Lithofin WAX-OFF
Calcium deposits, rust stains	Lithofin KF Cement Residue Remover
Dark deposits	Lithofin MN Outdoor Cleaner

### Please Note:

- △ Please follow the detailed instructions on the label.
- △ Greasy or waxy maintenance products may bind dirt and will affect the slip resistance properties of the surface.

This information should be considered to be informal and non-binding.  
The products must be used according to local conditions and materials.  
Instructions must be read carefully and followed closely. Always test  
the products in an inconspicuous area. (GB12.20gps)

If you require advice or are in any way unsure about  
these instructions, please call our  
**Technical Support Line at (01962) 732126.**

Your LITHOFIN-Dealer:

### ■ The Professional Solution

#### Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · Fax +44 (0)1962 735 373  
Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de [www.lithofin.co.uk](http://www.lithofin.co.uk)