

Cleaning and Maintaining Porcelain Tiles -outdoors-

Instructions for tiles with matte finishes

Porcelain stoneware is fired from finely prepared raw materials at high temperatures. As so-called outdoor ceramics, porcelain stoneware is increasingly used outdoors. The resulting high-density surfaces are hard-wearing and relatively insensitive. The right treatment right from the start brings out the properties of the ceramic flooring to the fullest and ensures you unadulterated enjoyment for many years.

Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1a

Initial cleaning of newly installed surfaces

Lithofin KF Cement Residue Remover leaves a clean and clear surface.



Coverage:
1 Ltr./30m²



Dilute product 1:4 with water.



Wipe surface with solution.



Rinse well with plenty of clear water and towel dry.

Erforderliche Geräte: Eimer, Mopp und Schrubber, Gummiabzieher oder Wassersauger

1b

Initial cleaning -drainable mortar-1-component systems



Coverage:
1Ltr./30m²



Dilute product 1:10 with water. apply to the surface and allow to work for 10 to 20 min. (20°C surface temperature). Scrub occasionally.



Rinse well with plenty of water.

1c

Initial cleaning -drainable mortar-2-component systems



Coverage:
1 Ltr./5m²



Apply product pure to the covering and leave on for approx. 60 minutes at surface temperatures of 20°C or slightly above. Scrub occasionally.



Rinse well with plenty of water.

Necessary equipment: bucket, mop, scrubbing brush.


2

Regular maintenance


Lithofin KF Intensive Cleaner maintains porcelain tile surfaces.



Add one squirt (20ml) to one bucket of water.



Wipe or scrub the surface with the solution and rinse well.



Allow to dry. Do not walk on surface during drying time.

Necessary equipment: bucket, mop.

Please follow the detailed instructions on the product labels.

Ref. 22002 Stand 2.26ik

Removal of plant-related discoloration as well as general impurities

Lithofin MN Outdoor Cleaner is a chlorine-containing, alkaline product with high-quality cleaning components. The special cleaner dissolves and removes organic discoloration, e.g. caused by leaves, flowers, fruits and pollen as well as all general soiling, including in the joint area.

- Apply undiluted
- Spread with garden sprayer or scrubbing brush or mop.
- The application time should be approx. 2 hours. (Do not allow solution to dry).
- Wash off with water and a brush.



Basic cleaning – removal of general dirt

Lithofin KF Intensive Cleaner is an alkaline special product with high-quality cleaning components. The special product is suitable for periodic basic cleaning, loosens and removes almost any type of general dirt.

- Apply diluted approx. 1:10.
- Spread with a scrubbing brush or mop.
- Leave on for approx. 20 minutes, scrubbing if necessary. (Do not allow solution to dry).
- Peel off with a rubber squeegee, pick up and rinse 1 to 2 times with plenty of water.



Note: For drainable 1K joints, Lithofin KF Intensive Cleaner must be applied in the specified dilution of 1:10 or higher.

Removal of special contaminants

Grease, oil, wax, tar, wood stains, paint, rubber strips, shoe abrasion	Lithofin WAX-OFF
Limescale deposits, rust stains	Lithofin KF Cement Residue Remover
Discoloration, impurities and other black deposits	Lithofin MN Outdoor Cleaner

Maintenance cleaning (regular)

Add a dash of Lithofin KF Intensive Cleaner to the cold or lukewarm mopping water.

This makes it easy and complete to remove the dirt that occurs normally.

- Apply to the floor with a damp cloth. Scrub the floor according to the soiling. Rinse off the dirt liquor.
- Allow to dry, do not walk on.

Please note:

Do not walk on surfaces during drying. Do not use cleaning and care products containing grease or wax, as these form deposits and lead to increased dirt adhesion and the formation of layers of dirt.

Please refer to the instructions for use.

This information can and should only provide non-binding advice.
The use of a product must be adapted to the local conditions and the surfaces to be treated.
The suitability of the product shall be determined on a sample area (GB2.26ik).

If you require advice or are in any way unsure about these instructions, please call our **Technical Support Line at (01962) 732126.**

Your LITHOFIN-Dealer:

■ The Professional Solution

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · Fax +44 (0)1962 735 373
Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de www.lithofin.co.uk