

Treatment of Nero Assoluto rough, honed, polished

Nero Assoluto is a fine-grained black basalt from southern Africa. Other trade names include Belfast Black and Nero Zimbabwe. There are limestone (Italy) and gabbro (Uruguay/India) under the same name, but they have different properties.

The flooring retains its naturally beautiful appearance through a natural stone-friendly treatment.

General information

Rough surfaces (flamed, blasted, etc.) have a gray color and thus a strong color deepening potential. This is why they are more sensitive in use, e.g. greasy fingers quickly leave dark spots.

Before grouting

To make it easier to wash off the grout on rough surfaces, apply Lithofin STAINSTOP >W<* thinly before grouting.

Final construction cleaning

A clean, clear surface can be obtained by cleaning with Lithofin MN Power-Clean diluted 1:10. For polished and finely ground surfaces, remove light cement residues at the same time.



Only if unavoidable, treat stubborn residues of grout with Lithofin MN Builders' Clean. Dilute the cleaner to approx. 1:10, apply to the pre-wetted surface, brush through and rinse immediately afterwards with plenty of water.

Removal of special contaminants

oil, grease, residues of care products	Lithofin MN Power-Clean
tar, wax, wood stains, sealings	Lithofin WAX-OFF
deep-seated oil stains	Lithofin OIL-EX
limescale deposits	Lithofin KF Ceramic-Clean

Regular maintenance



For normal use, it is sufficient to wipe the pavement regularly with a damp cloth. Add Lithofin MN Wash & Clean to the wiping water – this way you clean and care in one go. Rough surfaces in particular become more colourful and less sensitive over time. Strongly grease-dissolving agents and

leaching soft soaps are not suitable for long-term care.

For the regular maintenance of kitchen worktops, washbasins, window sills, etc., we recommend Lithofin MN Easy-Clean.

This information can and should only provide non-binding advice. The use of a product must be adapted to the local conditions and the surfaces to be treated. The suitability of the product shall be determined on a test area.

*For industrial and professional use only.

Additional easy-care equipment

Heavily used and stain-prone surfaces such as floors, tables, kitchen worktops, etc. need a special impregnation. This makes the surface water and oil repellent. This prevents stains and makes other contaminants easier to remove. The natural stone becomes even easier to care for and remains beautiful and well-maintained for years. Lithofin MN Stain-Stop*, which has very good water and oil repellency, meets these requirements. The surfaces treated with the solvent-based special impregnation are harmless to health after drying.

Important: All impregnations must only be used on completely dried and absorbent surfaces. The creation of a test area is recommended.



times.

Procedure: Use a mop or brush for smooth, polished and finely ground surfaces, a sealing brush or surface brush for rough surfaces. Apply the product evenly and thinly, avoiding streaks and puddles and brushing over evenly several



Remove excess completely before drying (approx. 10 to 15 minutes). To do this, peel off diagonally to the joints with a rubber squeegee and/or immediately pick up or polish off any remaining residue with absorbent cloths.

Coverage: approx. 20 to 30 m²/Litre depending on the surface. A repeat of the impregnation after a maximum of three years is recommended.

LITHOFIN special products for marble and other natural stones are only available in natural stone retailers.

Technical Support Line at

0044 (0)1962 732 126



GB7.26 / Ref. 46020 Edition D3.20as

Your LITHOFIN-Dealer:

The Professional Solution

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 1962 732 126 · sales@lithofin.co.

Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de

www.lithofin.co.uk