

Cleaning - Protecting - Maintaining

Limestone sanded -indoors-

Instructions for light, cream-coloured mostly oolitic limestones

Various limestones are commercially available as limestone. Due to their different origins, they have different properties (hardness, absorbency, etc.). What they have in common is the unique natural stone look, as well as the need for surface treatment. This beautifies the appearance, ensures contemporary performance properties and ensures you many years of unadulterated enjoyment with this classic natural stone.

The 3 steps at a glance, detailed information see page 2

1



Coverage:
1Litre/50m²

Before grouting: Impregnation makes it easier to wash off the joint material later

Initial cleaning of new surfaces *used surfaces: see page 2*

Lithofin MN Power-Clean - acid-free - removes greasy general dirt and much more.



Dilute product with water 1:10.



Brush the floor vigorously with a damp wetness, then mop up.



Wash well with fresh water.



Allow the surface to dry well.

Note:

On rough surfaces, stubborn haze can be removed with Lithofin MN Builders' Clean (diluted min. 1:15). Please do a preliminary test.

Required equipment: bucket, mop and scrubber, rubber squeegee or water vacuum cleaner

2




Coverage:
1Litre/8m²

Protective treatment against stains *Pre-cleaning of used surfaces: see page 2*

Lithofin MN Stain-Stop >ECO< repels water and oil and makes maintenance easier



Please note.
For industrial and professional use only.



Transfer product to tub or bucket.




Apply evenly with a squeegee.



Spread or completely remove excess, streaks, puddles



Leave to dry for approx. 45 mins. Do not commit.



Protect from moisture for approx. 24 hours

Required equipment: Tub or bucket with scraper rail, short-pile mop, brush, cleaning cloths

3



1Liter

Regular maintenance for *further information, see page 2*

Lithofin MN Wash & Clean - used regularly - maintains well-maintained surfaces.



Add one squirt (20ml) to one bucket of water.



Wipe the floor with a damp cloth. Do not wipe with water.



Allow to dry. Do not walk on surface during drying time.

Note:

In case of heavy soiling, wipe occasionally with Lithofin MN Power-Clean (diluted 1:20.)

Required equipment: bucket, mop or similar

Please refer to the instructions on the packaging.

GB7.26 / Ref. 47001 Edition D3.20as

Newly laid areas

Before grouting: Apply Lithofin MN Stain-Stop >ECO<* thinly to the dry surface once before grouting and leave to dry for approx. 6 hours. Washing off the grout is then easier because the covering is water-repellent. When grouting the flooring, the joint material should be carefully and completely washed off the surface.

1 Pre-cleaning for protective treatment of used, heavily soiled surfaces

The treatment of a surface that has already been used requires careful pre-cleaning.

- Dilute Lithofin MN Power-Clean with water up to 1:10, depending on the soiling, apply generously with a scrubbing brush or cloth and leave on for 5-10 minutes.
- Then brush well (scrubber or brusher) and wait another 5 minutes.
- Add water under brushes and absorb or vacuum liquid.
- Wash well twice with clean water until all detergent residues are completely removed.

After a few days of drying time, you can carry out the protective treatment.

Removal of special contaminants

oil, grease, residues of floor care products	Lithofin MN Power-Clean
tar, wax, wood stains, sealants	Lithofin WAX-OFF
deep-seated oil stains	Lithofin OIL-EX
rust stains (all surfaces)	Lithofin Rust-EX
limescale deposits (only for rough surfaces)	Lithofin MN Builders' Clean (min. diluted 1:20)

2a Further information on the protective treatment against stains

The natural stone surface becomes much easier to maintain and its beautiful appearance is retained for many years.

The active ingredients are harmless to health after drying.

A repeat of the impregnation after about 4 to 5 years is recommended. Suitable for indoor and outdoor use.

Important:

- **Create a test area beforehand.** Non-absorbent or damp surfaces cannot be impregnated.
- Impregnations should only be applied to completely dried surfaces, otherwise the product cannot be absorbed into the surface.
- Wipe off excess product from the surface carefully and completely, as this is no longer possible after drying.
If the cloth is already beginning to dry, moisten it with product if necessary.
- Impregnation does not protect against the effects of acids.

2b Alternative surface treatment

Sealing is a layer-forming treatment that gives surfaces a glossy protective film.

This must be renewed or refreshed from time to time. Layer-forming products are only suitable for indoor use and change the slip resistance of the surface.

In the case of very absorbent stone, pre-impregnate with Lithofin MN Stain-Stop >ECO<* before applying the sealant.

The order quantity and the number of orders depend on the properties of the stone.

Lithofin MN Care-Seal forms a silky matt glossy protective film that only slightly enhances the colour.

Gives rough to finely ground flooring an elegant finish. From time to time, a new treatment is necessary.

Important notes: Please follow the detailed instructions on the packaging.

△ Limestone, like any limestone, is made up of acidic substances such as vinegar, lemon juice, ketchup, wine, sparkling wine, acidic cleaners, etc. Avoid contact of these substances with limestone.

TIP: Avoid leaching, highly grease-dissolving cleaners, as well as products that form layers or residues leave behind, they impair the well-groomed appearance of natural stone and make it difficult to maintain.

*For industrial and professional use only.

This information can and should only provide non-binding advice.

The use of a product must be adapted to the local conditions and the surfaces to be treated.

The suitability of the product shall be determined on a test area.

If you require advice or are in any way unsure about these instructions, please call our
Technical Support Line at 0044 (0)1962 732 126

Your LITHOFIN-Dealer:

The Professional Solution

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alresford, Hampshire SO24 9QF · Phone: +44 1962 732 126 · sales@lithofin.co.

Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de

www.lithofin.co.uk