

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Lithofin STAINSTOP > W <

1.2 Relevant identified uses of the substance or mixture and uses advised against**Relevant identified uses**

Mixture Impregnation, aqueous solution

1.3 Details of the supplier of the safety data sheet

Supplier : Lithofin AG
Street : Heinrich-Otto-Str. 36
Postal code/City : 73240 Wendlingen
Country : GERMANY
Telephone : +49 7024 9403 0
Telefax : +49 7024 9403 40
Contact : Technical Department
E-mail : info@lithofin.de

Emergency telephone number : +49 7024 9403 0
(Only available during office hours)

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP]**

None

Additional information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

Remark

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

2.2 Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]****Special rules for supplemental label elements for certain mixtures**

EUH210 Safety data sheet available on request.

Other labelling**2.3 Other hazards****Adverse environmental effects**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

2.4 Additional information

see section 12.5

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

ETHANEDIOL ; REACH No. : 01-2119456816-28-xxxx ; EC No. : 203-473-3; CAS No. : 107-21-1

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : STOT RE 2 ; H373 Acute Tox. 4 ; H302

PROPAN-2-OL ; REACH No. : 01-2119457558-25-xxxx ; EC No. : 200-661-7; CAS No. : 67-63-0

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

None (below the concentration limit)

Contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH

None (below the concentration limit)

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Protect uninjured eye. In case of eye irritation consult an ophthalmologist.

Following ingestion

When in doubt or if symptoms are observed, get medical advice. Rinse mouth thoroughly with water. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet ABC-powder Foam

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture**Hazardous combustion products**Carbon monoxide Carbon dioxide (CO₂) Hydrogen fluoride Fluoropolymers**5.3 Advice for firefighters**

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Coordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up**For cleaning up**

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation.

Other information

Clear spills immediately.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

Protective measures

not useable after freezing. Inhalation of vapours or spray/mists Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Measures to prevent fire

The product is not: Flammable Usual measures for fire prevention.

Fire class :

-

Shake well before use

nein

Advices on general occupational hygiene

P362+P364 - Take off contaminated clothing and wash it before reuse.

7.2 Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Trade name : Lithofin STAINSTOP > W <**Revision date :** 04.06.2025**Version (Revision) :** 8.0.0 (7.0.0)**Print date :** 15.07.2025

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Hints on joint storage**Storage class (TRGS 510) :** 10**Protect from frost** ja**Recommended storage temperature** 5 - 25 °C**Further information on storage conditions**

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

Protect against : Frost**7.3 Specific end use(s)****Recommendation**

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

ETHANEDIOL ; CAS No. : 107-21-1

Limit value type (country of origin) : KZW (A)

Limit value : 20 ppm / 52 mg/m³

Peak limitation : 5Mow, 8x

Remark : H

Version :

Limit value type (country of origin) : TMW / TWA (A)

Limit value : 10 ppm / 26 mg/m³

Remark : H

Version :

Limit value type (country of origin) : STEL (AUS)

Limit value : 40 ppm / 104 mg/m³

Remark : Sk

Version :

Limit value type (country of origin) : TWA (AUS)

Limit value : 20 ppm / 52 mg/m³

Remark : Sk

Version :

Limit value type (country of origin) : STEL (B)

Limit value : 40 ppm / 104 mg/m³

Remark : D, M

Version :

Limit value type (country of origin) : TWA (B)

Limit value : 20 ppm / 52 mg/m³

Remark : D, M

Version :

Limit value type (country of origin) : KZG / STEL (CH)

Limit value : 20 ppm / 52 mg/m³

Remark : SSc, H

Version :

Limit value type (country of origin) : MAK (CH)

Limit value : 10 ppm / 26 mg/m³

Remark : SSc, H

Version :

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 26 mg/m³
Peak limitation : 2(I)
Remark : H,Y
Version : 17.06.2024

Limit value type (country of origin) : TWA (DK)
Limit value : 10 ppm / 26 mg/m³
Remark : EH
Version :

Limit value type (country of origin) : VLA-EC / STEL (E)
Limit value : 40 ppm / 104 mg/m³
Remark : via dérmica, VLI
Version :

Limit value type (country of origin) : VLA-ED / TWA (E)
Limit value : 20 ppm / 52 mg/m³
Remark : via dérmica, VLI
Version :

Limit value type (country of origin) : STEL (EC)
Limit value : 40 ppm / 104 mg/m³
Remark : Skin
Version : 09.03.2022

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 52 mg/m³
Remark : Skin
Version : 09.03.2022

Limit value type (country of origin) : VLEP 8h / TWA (F)
Limit value : 20 ppm / 52 mg/m³
Version :

Limit value type (country of origin) : VLEP CT / STEL (F)
Limit value : 40 ppm / 104 mg/m³
Version :

Limit value type (country of origin) : STEL (GB)
Limit value : 40 ppm / 104 mg/m³
Remark : Sk
Version :

Limit value type (country of origin) : TWA (GB)
Limit value : 20 ppm / 52 mg/m³
Remark : Sk
Version :

Limit value type (country of origin) : ÁK (H)
Limit value : 20 ppm / 52 mg/m³
Remark : b,i
Version :

Limit value type (country of origin) : CK-érték / STEL (H)
Limit value : 40 ppm / 104 mg/m³
Remark : b, i
Version :

Limit value type (country of origin) : STEL (I)
Limit value : 40 ppm / 104 mg/m³
Remark : Cute
Version :

Limit value type (country of origin) : TWA (I)
Limit value : 20 ppm / 52 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Remark : Cute
Version :

Limit value type (country of origin) : OELV 15 min / STEL (IRL)
Limit value : 40 ppm / 104 mg/m³
Remark : Sk, IOELV
Version :

Limit value type (country of origin) : OELV 8h / TWA (IRL)
Limit value : 20 ppm / 52 mg/m³
Remark : Sk, IOELV
Version :

Limit value type (country of origin) : STEL (N)
Limit value : 40 ppm / 104 mg/m³
Remark : S
Version :

Limit value type (country of origin) : TWA (N)
Limit value : 20 ppm / 52 mg/m³
Remark : HE
Version :

Limit value type (country of origin) : TGG 15 min / STEL (NL)
Limit value : 40 ppm / 104 mg/m³
Remark : H
Version :

Limit value type (country of origin) : TGG 8 uur / TWA (NL)
Limit value : 20 ppm / 52 mg/m³
Remark : H
Version :

Limit value type (country of origin) : Ceiling (NZ)
Limit value : 50 ppm / 127 mg/m³
Version :

Limit value type (country of origin) : NDSCH (PL)
Limit value : 50 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : NDS (PL)
Limit value : 15 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : STEL (ROK)
Limit value : 100 mg/m³
Remark : C
Version :

Limit value type (country of origin) : NIOSH REL Ceiling (USA)
Remark : Appendix D (Ceiling 50 ppm)
Version :

Limit value type (country of origin) : OSHA PEL TWA (USA)
Remark : Appendix G (Ceiling 50 ppm)
Version :

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type (country of origin) : KZW (A)
Limit value : 800 ppm / 2000 mg/m³
Peak limitation : 15Miw, 4x
Version :

Limit value type (country of origin) : TMW / TWA (A)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Limit value : 200 ppm / 500 mg/m³
Version :

Limit value type (country of origin) : STEL (AUS)
Limit value : 400 ppm / 984 mg/m³
Version :

Limit value type (country of origin) : TWA (AUS)
Limit value : 200 ppm / 491 mg/m³
Version :

Limit value type (country of origin) : STEL (B)
Limit value : 400 ppm / 1000 mg/m³
Version :

Limit value type (country of origin) : TWA (B)
Limit value : 200 ppm / 500 mg/m³
Version :

Limit value type (country of origin) : BAT (CH)
Parameter : Acetone / Whole blood (B) / End of exposure or end of shift
Limit value : 25 mg/l / 0,4 mmol/L
Version :

Limit value type (country of origin) : KZG / STEL (CH)
Limit value : 400 ppm / 1000 mg/m³
Remark : SSC, B
Version :

Limit value type (country of origin) : MAK (CH)
Limit value : 200 ppm / 500 mg/m³
Remark : SSC, B
Version :

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 200 ppm / 500 mg/m³
Peak limitation : 2(II)
Remark : Y
Version : 17.06.2024

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Whole blood (B) / End of exposure or end of shift
Limit value : 25 mg/l
Version : 10.10.2024

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Urine (U) / End of exposure or end of shift
Limit value : 25 mg/l
Version : 10.10.2024

Limit value type (country of origin) : TWA (DK)
Limit value : 200 ppm / 490 mg/m³
Version :

Limit value type (country of origin) : VLA-EC / STEL (E)
Limit value : 400 ppm / 1000 mg/m³
Remark : VLB, s
Version :

Limit value type (country of origin) : VLA-ED / TWA (E)
Limit value : 200 ppm / 500 mg/m³
Remark : VLB, s
Version :

Limit value type (country of origin) : VLEP CT / STEL (F)
Limit value : 400 ppm / 980 mg/m³
Version :

(EN / D)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Limit value type (country of origin) : STEL (GB)
Limit value : 500 ppm / 1250 mg/m³
Version :

Limit value type (country of origin) : TWA (GB)
Limit value : 400 ppm / 999 mg/m³
Version :

Limit value type (country of origin) : ÁK (H)
Limit value : 200 ppm / 500 mg/m³
Remark : b, i
Version :

Limit value type (country of origin) : CK-érték / STEL (H)
Limit value : 400 ppm / 1000 mg/m³
Remark : b, i
Version :

Limit value type (country of origin) : OELV 15 min / STEL (IRL)
Limit value : 400 ppm
Remark : Sk
Version :

Limit value type (country of origin) : OELV 8h / TWA (IRL)
Limit value : 200 ppm
Remark : Sk
Version :

Limit value type (country of origin) : TWA (N)
Limit value : 100 ppm / 245 mg/m³
Version :

Limit value type (country of origin) : STEL (NZ)
Limit value : 500 ppm / 1230 mg/m³
Version :

Limit value type (country of origin) : TWA (NZ)
Limit value : 400 ppm / 983 mg/m³
Version :

Limit value type (country of origin) : NDSCH (PL)
Limit value : 1200 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : NDS (PL)
Limit value : 900 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : STEL (ROK)
Limit value : 400 ppm
Version :

Limit value type (country of origin) : TWA (ROK)
Limit value : 200 ppm
Version :

Limit value type (country of origin) : NIOSH REL STEL (USA)
Limit value : 500 ppm / 1225 mg/m³
Version :

Limit value type (country of origin) : NIOSH REL TWA (USA)
Limit value : 400 ppm / 980 mg/m³
Version :

Limit value type (country of origin) : OSHA PEL TWA (USA)
Limit value : 400 ppm / 980 mg/m³

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Remark : Appendix G (STEL 500 ppm, 1225 mg/m³)

Version :

PYRIDINE-2-THIOL 1-OXIDE, SODIUM SALT ; CAS No. : 3811-73-2

Limit value type (country of origin) : KZW (A)

Limit value : 4 mg/m³

Peak limitation : 15Miw, 4x

Remark : H

Version :

Limit value type (country of origin) : TMW / TWA (A)

Limit value : 1 mg/m³

Remark : H

Version :

Limit value type (country of origin) : KZG / STEL (CH)

Parameter : E: inhalable fraction

Limit value : 0,4 mg/m³

Remark : SSC, H

Version :

Limit value type (country of origin) : MAK (CH)

Parameter : E: inhalable fraction

Limit value : 0,2 mg/m³

Remark : SSc,H

Version :

Limit value type (country of origin) : TWA (DK)

Limit value : 1 mg/m³

Remark : H

Version :

DNEL-/PNEC-values**DNEL/DMEL**

ETHANEDIOL ; CAS No. : 107-21-1

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 7 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 53 mg/kg bw/day

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 35 mg/m³

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 106 mg/kg bw/day

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Short-term

Limit value : 51 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 26 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	319 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	178 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	89 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	888 mg/kg bw/day
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	1000 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	500 mg/m ³

PNEC

ETHANEDIOL ; CAS No. : 107-21-1

Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	10 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	10 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	1 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	20,9 mg/kg
Limit value type :	PNEC (Soil)
Limit value :	1,53 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	199,5 mg/l

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type :	PNEC (Aquatic, freshwater)
Limit value :	140,9 mg/l
Limit value type :	PNEC (Aquatic, intermittent release)
Limit value :	140,9 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Limit value :	140,9 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	552 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	552 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	28 mg/l
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	2251 mg/l

8.2 Exposure controls

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Appropriate engineering controls

Ensure adequate ventilation of the storage area.
Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Eye/face protection

Usually no personal eye/face protection necessary. Eye/face protection necessary at: Splashes, Contact with eyes, Spray application.

Suitable eye protection

Eye glasses with side protection goggles

Required properties

EN 166

Skin protection

Usually no personal skin protection necessary. Skin protection necessary at: Splashes, Contact with skin, Spray application.

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : NBR (Nitrile rubber), 0,4mm, >8h; Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

Recommended glove articles : Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures : Check leak tightness/impermeability prior to use.

Remark : Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

Body protection

Protective clothing.

Suitable protective clothing : Chemical protection clothing Chemical resistant safety shoes

Required properties : acid-resistant. alkali-resistant.

Protective clothing. : EN 13034 EN 14605

Chemical resistant safety shoes : EN ISO 20345

Remark : Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (EN 136/140) Combination filtering device ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid

Colour : light yellow

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Odour : unspecific

Safety characteristics

Melting point/freezing point :	(1013 hPa)	approx.	-10	°C	
Initial boiling point and boiling range :	(1013 hPa)	approx.	88	°C	
Decomposition temperature :	(1013 hPa)		not determined		
Flash point :		approx.	38	°C	closed cup (EN ISO 3679)
Auto-ignition temperature :			not determined		
Sustaining combustion			No		UN Test L2:Sustained combustibility test
Lower explosion limit :			not determined		
Upper explosion limit :			not determined		
Vapour pressure :	(50 °C)	<	3000	hPa	
Density :	(20 °C)		1	g/cm ³	Pyknometer (DIN EN ISO 2811-1)
Relative density :	(20 °C)		not determined		
Solvent separation test :	(20 °C)	<	3	%	Test L1: Solvent separation test (UN)
Water solubility	(20 °C)		miscible		
Fat solubility :	(20 °C)		Not determined.		
pH :		approx.	5		DIN 19268
log P O/W :			not determined		(Mixture)
Flow time :	(23 °C)	approx.	13	s	ISO cup 4 mm (DIN EN ISO 2431)
Odour threshold :			not determined		
Vapourisation rate :			not determined		
VOC content-EC			19,6	Weight-%	*
VOC content-EC			197	g/l	*
VOC-France			A+		Décret no 2011-321 du 23 mars 2011
Flammable solids :			Not determined.		

(* VOC-EC = „Volatile organic compound (VOC)“ means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

Trade name : Lithofin STAINSTOP > W <**Revision date :** 04.06.2025**Version (Revision) :** 8.0.0 (7.0.0)**Print date :** 15.07.2025**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Acute oral toxicity

Parameter :	LD50 (ETHANEDIOL ; CAS No. : 107-21-1)
Exposure route :	Oral
Species :	Rat
Effective dose :	7712 mg/kg
Parameter :	LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Oral
Species :	Rat
Effective dose :	5840 mg/kg
Method :	OECD 401

Acute dermal toxicity

Parameter :	LD50 (ETHANEDIOL ; CAS No. : 107-21-1)
Exposure route :	Dermal
Species :	Mouse
Effective dose :	> 3500 mg/kg bw/day
Parameter :	LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	13900 mg/kg
Method :	OECD 402

Acute inhalation toxicity

Parameter :	LC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 2500 mg/m ³
Exposure time :	6 h
Parameter :	LC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	25000 mg/m ³
Exposure time :	6 h
Method :	OECD 403

Specific effects (Longterm animal experiment)

There are no data available on the preparation/mixture itself.

Corrosion

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Repeated dose toxicity (subacute, subchronic, chronic)

There are no data available on the preparation/mixture itself.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Carcinogenicity**

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Trade name : Lithofin STAINSTOP > W <**Revision date :** 04.06.2025**Version (Revision) :** 8.0.0 (7.0.0)**Print date :** 15.07.2025**STOT-single exposure**

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity**

Based on available data, the classification criteria are not met.

Acute (short-term) fish toxicity

Parameter :	LC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Species :	Fish
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	72860 mg/l
Exposure time :	96 hour(s)
Parameter :	LC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species :	Fish
Evaluation parameter :	Acute (short-term) fish toxicity
Effective dose :	9640 mg/l
Exposure time :	96 hour(s)
Method :	OECD 203

Chronic (long-term) fish toxicity

Parameter :	NOEC (ETHANEDIOL ; CAS No. : 107-21-1)
Species :	Fish
Evaluation parameter :	Chronic (long-term) fish toxicity
Effective dose :	8590 mg/l
Exposure time :	7 day(s)
Parameter :	NOEC (PROPAN-2-OL ; CAS No. : 67-63-0)
Species :	Fish
Evaluation parameter :	Chronic (long-term) fish toxicity
Effective dose :	> 1000 mg/l
Exposure time :	28 day(s)

Acute (short-term) toxicity to aquatic invertebrates

Parameter :	EC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Species :	Daphnia
Evaluation parameter :	Acute (short-term) toxicity to aquatic invertebrates
Effective dose :	> 100 mg/l
Exposure time :	48 hour(s)
Method :	OECD 202
Parameter :	EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species :	Daphnia
Evaluation parameter :	Acute (short-term) toxicity to aquatic invertebrates
Effective dose :	> 10000 mg/l
Exposure time :	24 hour(s)
Method :	OECD 202

Chronic (long-term) toxicity to aquatic invertebrate

Parameter :	NOEC (ETHANEDIOL ; CAS No. : 107-21-1)
Species :	Daphnia

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 8590 mg/l
Exposure time : 7 day(s)
Parameter : NOEC (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Daphnia
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : > 1000 mg/l
Exposure time : 21 day(s)

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 6500 - 13000 mg/l
Exposure time : 96 hour(s)

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Algae
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria
Effective dose : 1800 mg/l
Exposure time : 7 day(s)

Sewage treatment plant

Observe local regulations concerning effluent treatment.

12.2 Persistence and degradability

There are no data available on the preparation/mixture itself.

Biodegradation

There are no data available on the preparation/mixture itself.

12.3 Bioaccumulative potential

There are no data available on the preparation/mixture itself.

12.4 Mobility in soil

There are no data available on the preparation/mixture itself.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

There are no data available on the preparation/mixture itself.

12.8 Additional ecotoxicological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of waste according to applicable legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV) : 07 01 99 (wastes not otherwise specified)

After intended use

Do not allow to enter into surface water or drains. Non-contaminated packages may be recycled. Packing which

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

cannot be properly cleaned must be disposed of. Delivery to an approved waste disposal company.

Disposal operations

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

Not required.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures (clp)

DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste (2000/532/EC) EN 2:1992 (DIN EN 2:2005-01)

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 40, 75

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Other regulations (EU)

Regulation (EC) No. 648/2004 [Detergents regulation]

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

Regulation (EU) 2024/590 on substances that deplete the ozone layer

Not listed/not relevant.

Contains the following substances that deplete the ozone layer: -

Regulation (EC) 2019/1021 [POP Regulation]

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

Not listed/not relevant.

Name of the persistent organic pollutant (POP): -

Regulation (EU) 2019/1148 (marketing and use of explosives precursors)

Not listed/not relevant.

Regulation (EU) 649/2012 (PIC)

Not listed/not relevant.

Chemicals qualifying for PIC notification: -

National regulations

Observe in addition any national regulations!

Germany:

TRGS 400 (Risk assessment for activities involving hazardous substances)

TRGS 500 (Protective measures)

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Other regulations, restrictions and prohibition regulations

Switzerland

VOCV-Regulation

Maximum VOC content (Switzerland) : 9,7 Weight-% according to VOCV

15.2 Chemical Safety Assessment

For this substance/mixture a chemical safety assessment has not been carried out.

15.3 Additional information

SECTION 16: Other information

16.1 Indication of changes

02. Label elements · 07. Hints on joint storage - Storage class · 08. Occupational exposure limit values · 15. Restrictions on use · 15. Water hazard class

16.2 Abbreviations and acronyms

ABC-Pulver	Extinguishing powder for fire class A, B and C
ABEK-P1	combination filter
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AVV	Abfallverzeichnis-Verordnung (Waste Regulation)
AWSV	Ordinance on facilities for the handling of substances hazardous to water
BGR	BG rules and regulations
ca.	circa
CAS	Chemical Abstracts Service
CLP	classification, labelling and packaging
CMR	Carcinogen, mutagen or toxic for reproduction
DIN	German Institute for Standardization
DNEL	Derived No-Effect Level
EAK/EWC/EAC/CWR/CER	European Waste Catalogue
EC50 / CE50	Effective Concentration 50%
EG / EC / CE	European Community
EN	European Standard
EUH	supplemental hazard statement of the european union
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

GHS / SGH	Globally Harmonised System
H-Sätze	hazard statements
IATA-DGR	International Air Transport Association-Dangerous Goods Regulations
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization-Technical Instructions
IMDG-Code	International Maritime Dangerous Goods Code
ISO	International Organization for Standardization
LC50 / CL50	Lethal Concentration 50%
LD50 / DL50	Lethal Dose 50%
log P O/W	Partition coefficient n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (marine pollution)
NOAEL (DSET)	No observed adverse effect level
NOEC (CSEO)	No observed effect concentration
Nr.	Number
OECD	Organisation for Economic Co-operation and Development
PBT	persistent, bioaccumulative and toxic
pH	Potentia hydrogenii
PIC	prior informed consent
PNEC	Predicted No-Effect Concentration
POP	Persistent organic pollutants
P-Sätze	precautionary statements
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	International Carriage of Dangerous Goods by Rail
STEL / LECT	short-term exposure limit
TRGS	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
TWA / MPT	time-weighted average
UN/ONU	United Nations
VOC/COV/VOS/LZO	Volatile Organic Compound
VOCV	Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)
vPvB	very persistent and very bioaccumulative
WGK	Wassergefährdungsklasse (Water hazard class)

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
ECHA: Registered substances (<https://echa.europa.eu/information-on-chemicals/registered-substances>)
REACH Article 59: Candidate List of substances of very high concern for Authorisation
(<https://echa.europa.eu/candidate-list-table>)

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data.
Hazard statements for health hazards : Calculation method.
Hazard statements for environmental hazards : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

Safety Data Sheet

(EN / D)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Lithofin STAINSTOP > W <

Revision date : 04.06.2025

Version (Revision) : 8.0.0 (7.0.0)

Print date : 15.07.2025

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
