

## Lithofin KF Intensive Cleaner for ceramic and porcelain tiles

### Description

A special product from the LITHOFIN range for ceramic tiles and porcelain stoneware (KF). Alkaline cleaning concentrate with a balanced combination of biodegradable cleaning components and highly effective grease and dirt-dissolving additives.

### Features

Lithofin KF Intensive Cleaner dissolves and removes even stubborn general dirt, oil and grease films, rubber and shoe abrasion, polymer and wax layers, self-shining emulsions, etc.

#### Technical data:

Density: approx. 1.1 g/cm<sup>3</sup>

Appearance: clear, slightly brownish liquid

Smell: slightly citrusy-like

pH value: approx. 14 (concentrate)

Solubility in water: 100%.

### Scope of application

For thorough cleaning of heavily soiled or incorrectly maintained ceramic coverings of all kinds, indoors and outdoors. For regular maintenance cleaning of highly stressed, heavily soiled surfaces. For occasional use on exposed surfaces where normal maintenance with Lithofin KF Conditioning Cleaner is not fully sufficient. Can be used in food processing plants, kitchens and occupied rooms.

### Processing as a basic round cleaner

Depending on the soiling, apply Lithofin KF Intensive Cleaner pure or diluted with water up to approx. 1:10. Spread with a scrubbing brush or mop and leave on for about 10 to 20 minutes, scrubbing if necessary. Do not allow the solution to dry. Remove with a rubber squeegee, pick up and wash 1 to 2 times with plenty of clean water.

### Processing as a maintenance cleaner

Manual: approx. 100 to 200 ml / 10 litres of wiper water. Remove with a rubber squeegee, pick up and wash 1 to 2 times with plenty of clean water. In the automatic cleaning machine (scrubber drier): approx. 300 to 400 ml / 10 litres of water, sufficient for approx. 100 to 150 m<sup>2</sup> area. It should be noted that the surfaces get well wet to ensure that the dirt is loosened and absorbed.

**Caution:** Do not use on polished marble, anodised, lacquered surfaces and other alkali-sensitive surfaces. It is recommended to create a test area in an inconspicuous place.

Be careful with drainable paving joint material in outdoor areas. Sample area required.

**Coverage:** Depending on soiling approx. 10 to 15 m<sup>2</sup> / litre for concentrated application, approx. 50 to 300 m<sup>2</sup> / litre for diluted application.

**Note:** For regular maintenance of lightly to normally soiled surfaces, we recommend Lithofin KF Conditioning Cleaner. An occasional deep cleaning with Lithofin KF Ceramic-Clean can be beneficial.

### Storage

Cool and sealed, can be stored for up to approx. 5 years.

### Environmental protection

The surfactants are biodegradable in accordance with regulation (EC) No. 648/2004 (detergents regulation).

**Disposal:** The container is made of environmentally friendly polyethylene (PE) and is recyclable. Rinsed containers can be disposed of and recycled via the recyclable material collection system (see note on label).

For information on labelling, transport and disposal, please refer to the safety data sheet.

### Packaging units (PU)

- a) 1 liter bottle with child-resistant cap (10 pcs. in a box)
- b) 5 liter canister (2 pcs. in a box)
- c) 10 liter canister (single)

Please note that the environmental and safety information applies to the (concentrated) product in delivery form. If dilution is appropriate for the application, the classification may change. This information can and should only provide non-binding advice. The use of the products must be adapted to the local conditions and the surfaces to be treated. If there is no experience and in all cases of doubt, the product should be tried out in an inconspicuous place beforehand. (AUS-NZ2.26/9.25)