

Lithofin MN Slate-Oil for protecting and maintaining all types of slate

Description

A special product from the LITHOFIN range for natural stone (MN). The ready-to-use protection and care product contains high-quality waxes and resins dissolved in CHC-free solvents.

Features

Lithofin MN Slate-Oil significantly strengthens the natural colours, which emphasises the stone structure. The surfaces look more lively and are water-repellent at the same time. It creates a slight shine that can be increased by polishing. The colour-deepening effect allows existing stains to be covered well. The build-up of thicker layers is omitted, as a large part of the old layer is removed with each new application. Lithofin MN Slate-Oil is therefore ideal for regular maintenance.

Technical data:

Density: approx. 0.8 g/cm³

Flash point: >23°C (c.C.)

pH-Value: n.a.

Appearance: liquid clear, colorless

Odour: non-specific, aromatic

Solubility in water: not soluble

Scope of application

For the initial treatment of new surfaces such as window sills, tables, floors, stairs, etc., in order to give them a fresh appearance and protection. Also suitable for refreshing unsightly and lightened Slate areas. Ideally suited for regular maintenance to maintain the colourful appearance.

Substrates: Rough to finely ground surfaces made of all types of clay slate of different origins, especially Indian, African, Italian species as well as Holzmadener oil shale and the like. Only suitable for indoor use.

Processing

Shake the bottle lightly before use.

New areas: These must be well dried out. Spread Lithofin MN Slate-Oil evenly with a sponge or cloth and allow to dry.

Soiled or pre-treated surfaces:

Apply generously, dissolved after a few minutes

Rub off dirt with a dry cloth. Then reapply and let dry.

Note: It is best to create a small sample area beforehand.

Polishing can increase the shine.

If the result is unsatisfactory, reapply and distribute evenly.

Below 10°C, the product can flocculate. In this case, keep warm and shake until the solution is clear again.

Coverage: approx. 20 m²/litre depending on substrate

Drying time: approx. 10 minutes

Further treatment

Lithofin MN Slate-Oil also has a cleansing effect.

In the case of heavy soiling, Lithofin MN Power-Clean should be used as a basic cleaner.

For regular damp mopping of floor surfaces, we recommend Lithofin MN Wash & Clean.

Storage

Sealed, dry and at temperatures between 10 to 25°C.

Can be stored for up to 3 years.

Environmental protection

Contains solvents, free of chlorinated hydrocarbons.

Do not add to the wastewater.

Disposal: Product residues are hazardous waste.

The container is made of environmentally friendly tinplate and can be recycled. Dried-out, empty containers can be disposed of via recyclable material collection systems (see note on label).

For information on labelling, transport and disposal, please refer to the safety data sheet.

Packaging

a) 1 litre bottle with child-proof cap (10 per box)

b) 5 litre canister (2 per box)

Please note that the environmental and safety information applies to the (concentrated) product in delivery form. If dilution is appropriate for the application, the classification may change.

This information can and should only provide non-binding advice.

The use of the products must be adapted to the local conditions and the surfaces to be treated. If there is no experience and in all cases of doubt, the product should be tried out in an inconspicuous place beforehand. (EN11.25/9.25)