

Lithofin MN Cobble Wax

Description

A special product from the LITHOFIN-Range for marble and natural stone (MN). It is a ready-to-use wax system in paste form and contains natural and synthetic wax raw materials, which form a hard-wearing film.

Properties

Lithofin MN Cobble Wax is a solid paste, which is easy to apply and spread. It forms a surface wax layer, which can be polished when dry, and gives the background a colour-saturated, silky shine appearance. The surfaces are also less sensitive, easier to maintain and are made more attractive.

Technical Data

Density: 0.8 g/m³

pH-Value: n/a

Flashpoint: approx. 39°C (c.C)

Appearance: yellow-beige, solid

Odour: aromatic

Field of Use

For final treatment of floors in antique tumbled or cobbled marble with sand-blasted, acid or similarly treated surface.

To improve resistance to stains the surfaces should also be pre-treated with Lithofin MN Stain-Stop.

Treatment results in a strong colour, antique effect appearance. Lithofin MN Cobble Wax is also used for maintaining already waxed surfaces. It is not suitable for polished or surfaces treated with a topical sealant, or for external use.

Surface Requirements

The surface must be completely dry, clean, free of stains and absorbent. Cement films can be removed with Lithofin MN Builders' Clean. This treatment will make the surface rougher and open the pores of the stone, allowing the wax to penetrate more effectively.

Pre-treatment with Lithofin MN Stain-Stop is recommended, to improve resistance to stains. In this case apply Lithofin MN Cobble Wax immediately after about 1-2 hours drying time. The temperature of the surface must not be below 12°C.

Directions for Use

We strongly recommend applying a sample surface.

This shows what the result will be, and gives information on how much to apply, drying time etc.

Lithofin MN Cobble Wax is ready to use and can be worked directly out of the tin. Particularly with more impervious surfaces, it should be warmed up in a water-bath to liquefy it more. The fluid, warm wax will penetrate more deeply and give greater deepening of colour.

Apply evenly and thinly, spread and rub in with a fluff-free cloth. You may need to apply treatment twice with strongly absorbent, porous backgrounds. Polish with a brush or polishing pad when dry.

Drying time: approx. 2 hours to polishing, can have things put on it after about 12 hours. Where larger amounts are applied, extend the drying time to about 24 hours.

Coverage: For first treatment about 20 m²/litre depending on type of surface, about 40 m²/litre when re-waxing.

Further Treatment

Further care of the antique marble surface treated should be done with Lithofin MN Wash & Clean or Lithofin EASY-CARE, which should always be used with washing water. If the surface becomes matt or dull freshen up with Lithofin MN Care-Sheen or re-wax with Lithofin MN Cobble Wax.

Storage

Closed, cool and dry. Shelf life of approx. 3 years.

Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: waste code according to EWC/AVV 07 01 04*. Bottles/canisters are made of environmentally friendly tinplate and can be recycled (see information on label).

Safety

UFI: 39G0-80MR-R001-KNK0

Ingredients: natural and synthetic waxes, resins, hydrocarbons.

Labelling according to regulation (EC) 1272/2008(CLP):

GHS Symbol 02, 07 Warning

Contains Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, < 2% aromatics; Hydrocarbons, C9, aromatics;

Flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains (R)-P-MENTHA-1,8-DIEN ; 2-BUTANONOXIM. May produce an allergic reaction. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Use only outdoors or in a well-ventilated area. Call a POISON CENTER or doctor/physician if you feel unwell. Store locked up. Dispose of contents and container in accordance with local and national regulations. Product poses no health concerns once fully dried.

ADR 2019: labelling for transport

Unit	Label	Notes on freight papers
a)	LQ	none, due to limited quantities

Packaging

a) 1 litre tin with child-proof cap (10 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated). This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (GB7.19gps/5.19)