

Lithofin Steel-Clean cleans, protects and maintains stainless steel

Description

A special product from the LITHOFIN range for households and businesses. Cleaning and care product based on high-quality raw materials.

Features

Highly active ingredients quickly dissolve dirt, oils and greases, so that even finger marks can be easily removed. In addition, dirt-repellent additives ensure reduced re-soiling with a long-term effect. The surface is given a streak-free brilliant shine.

Technical data:

Density: approx. 0.8 g/cm³

pH: n.a.

Appearance: colorless

Smell: fresh, perfumed

Solubility in water: not soluble

Scope of application

For regular maintenance of all stainless steel and similar metal surfaces in kitchens, stair railings, mailboxes, lamps and other objects. For brushed, polished and smooth surfaces. Suitable for indoor and outdoor use.

Processing

Shake the bottle before use. Put a few drops on a clean cloth and apply evenly and very thinly. In case of heavy soiling, leave on for a short time. Then polish with a dry, lint-free cloth or kitchen paper until it shines. Please note: A small sample area shows the effect. Do not apply to hot or adjacent sensitive surfaces. Polishing out excess product. For larger areas, work in sections.

Coverage: up to approx. 50 m² per bottle.

Note: You can remove limescale and water scale quickly and safely with Lithofin KF Ceramic-Clean.

Storage

Cool and dry, can be stored for up to approx. 3 years.

Environmental protection

Disposal: Empty containers can be disposed of via the recyclable material collection system (see note on label).

For information on labelling, transport and disposal, please refer to the safety data sheet.

Packaging units (PU)

a) 250 ml bottle (20 pieces in a box)

Please note that the environmental and safety information applies to the (concentrated) product in delivery form. If dilution is appropriate for the application, the classification may change. This information can and should only provide non-binding advice. The use of the products must be adapted to the local conditions and the conditions to be treated. surfaces. If there is no experience and in all cases of doubt, the product should be tried out in an inconspicuous place beforehand. (GB2.26/9.25gps)