

Lithofin Surface Disinfection

A special product from the LITHOFIN-Range. Universally applicable disinfectant cleaner for washable surfaces. The cleaner is formulated to be neutral, free of chlorine and acids and ready for use.

Properties

When used appropriately, the product kills bacteria, viruses and fungi that remain on surfaces.

Technical Data:

Density: approx. 1,0 g/cm³

pH-Value: approx. 8

Appearance: clear

Odour: unspecified

Field of Use

For all washable surfaces, such as furniture, vanities, door handles, telephones, refrigerators and much more.

Directions for Use

Lithofin Surface Disinfection is ready for use. Spray surface and ensure that it stays moist for the entire working time of at least 10 minutes. Wash off with water and leave to dry.

Please Note: Not suitable for disinfecting hands.

Coverage: 5-10 m² per 500 ml

Storage

Closed cool and dry. Store bottle standing up. Up to 2 years.

Environmental Protection

The contained surfactants are biodegradable according to regulation (EC) No. 648/2004 (detergents regulation).

Disposal: Waste code according to EWC/AVV 07 01 99. Bottles/canisters are made of environmentally friendly polyethylene and can be recycled (see information on label).

Safety

Use biocides safely. Always read the label and product information before use.

UFI: 0DP2-M0YJ-M00G-4CP5

Ingredients: Quaternary ammonium compounds, benzyl- C12-16-alkyldimethyl, chlorides 0,99 g / 100 g.

Labelling according to EU-Directive 1272/2008(CLP):

Toxic to aquatic life with long lasting effects. Keep out of reach of children. Dispose of contents/container in accordance with local and national regulations.

ADR 2019: labelling for transport

Unit	Label	Notes on freight papers
a)	--	none

Packaging (VE)

a) 500ml-bottle with Sprayer (10 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated). This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area (GB 3.20sz/ D3.20)